



Women of Rock

TECHNICAL REQUIREMENTS

General:

In our experience we have for the most part found the house techs/sound companies as provided by host orchestras to be highly competent professionals who know and understand the needs of their orchestra and their performance venue. As such we are comfortable in trusting their recommendation and expertise. Conceptually all Jeans 'n Classics productions are designed to feature the sound of the orchestra and as such the band and the orchestra should be equally sharing the musical picture as opposed to the orchestra being mixed into the back ground. The following are simply guidelines.

Strings

- Contact mics on all strings is ideal
- If impossible separate mics per player or minimally 1 mic per desk

Winds

- One mic per wind

Brass

- One mic per brass instrument

Percussion

- Individual mics on the congas/bongos area
- Ambient mics on the "toys" for wind chime, tambourine etc, where the player can approach the mic
- Individual mics on the vibes/marimbas area
- Timpani and bass drums may or may not need ambient mics depending on the venue



Monitors

- Generally we are trying to create a quiet on stage sound in order to give front of house the optimum orchestral head-room. Therefore in-ear monitor systems are ideal for the band and vocalists. (Some of our personnel will bring their own in-ear monitors).
- Small wedge monitors are preferred for the vocalists - four across the front line of the stage.
- In addition one for the Conductor. If you have additional monitors they would be beneficial near the brass and percussion sections.

-
Our drummer brings his own ears and mixer and will need 1 stereo XLR line (male) for monitor mix, instead of wedge (or 2 right/left XLR lines) - positioned on Hi Hat side plus 1 A.C. drop - positioned on Hi Hat side and 1 music stand (or mic stand)

We will need 8 separate monitor mixes for our personnel.

- Note – It is very important that the monitor operator be sensitive to the orchestra in keeping the monitor levels as low as our personnel are comfortable with.

Soundman

- A set of scores can be provided for the soundman if required in order to follow the arrangements.

Vocalist (s)

4 Vocal mics required (cordless) – numbered, in the wings, for entries and exits please. Vocalists will go back and forth from a front stage lead vocal station to a BG's vocal station.

In order to avoid mic stand movement, we will need to mic stands at the lead Station and three please in the BG's station.

Drums

Standard Yamaha 5 piece

(Choose from any of the following, in order of preference):

- Recording Custom
- Maple Custom
- Oak Custom
- Absolute Series (Birch, Maple, or Oak)

Or an equivalent DW 5 piece (i.e.; Collector's Series Maple)



Specifications:

- A. 22" or 20" Bass Drum
- B. 14" WOOD Snare Drum
(Any depth, NO PICCOLO)
- C. 10" Mounted Rack Tom (mounted on Bass Drum)
- D. 12" Mounted Rack Tom (mounted on Bass Drum)
- E. 14" Mounted or Freestanding Floor Tom (Mounted on Freestanding combination Cymbal/Tom stand)
*(10-12-14 Tom combination is preferred, other combinations will suffice:
8-10-12(mounted floor), or 10-12-16(freestanding floor)
MUST always have a 2" interval between Rack Toms, and at least a 2" interval between second Rack Tom and Floor Tom (NO 12-13 Rack Tom combination)
- F. 1 Yamaha/DW Snare Drum Stand
- G. 3 Yamaha/DW Cymbal Stands with boom option
- H. 1 Yamaha/DW Hi Hat Stand with clutch
- I. 1 Yamaha/DW or comparable PROFESSIONAL Drum Throne (Stool) – must be in PERFECT working condition.
- J. 1 Yamaha/DW Bass Drum Pedal (or Tama "Iron Cobra")
- K. 20" or 22" Ride Cymbal (Zildjian or Sabian only)
- L. 2 Crash Cymbals of different sizes, chosen from 14", 15", 16", 17" or 18" - dark or thin (Zildjian or Sabian only)
- M. 1 pair of 14" or 13" Hi Hat Cymbals (Zildjian or Sabian only)
- N. Heads:
 - Bass Drum Head should be Remo Pinstripe or Clear Ambassador or Clear Emperor (or comparable PROFESSIONAL Manufacturer – Evans/Aquarian) Resonant (Front) Head with hole
 - Snare Head MUST be Remo white coated Ambassador Batter (top) with Remo Clear Diplomat Snare Head (bottom)
 - Toms should be Remo Pinstripe or Clear Ambassador or Clear Emperor Top Heads, and Remo Clear Diplomat Bottom Heads (or comparable PROFESSIONAL Manufacturer – Evans/Aquarian)
- O. Drum Rug (suggested size: 8X8)
- P. 1 Drum Key
- Q. Plexiglass drum shield/encasing required
A drum shield with enough panels to completely surround the drum set, with the panels no less than 5 feet in height.



Electric Bass (Mitch Tyler)

Bass player to provide Behringer mixer and will need line from front of house
Bass player will use his own "in ears" or headphones

Bass guitar to be provided with strap.

4- String Fender Precision (American made preferred)

Guitar

Guitarist will bring processing equipment for electric guitar

A DI line will be required

A second DI line will be required for acoustic guitar

Keyboard/Piano

Grand piano or if not available then any of the following

Yamaha Motif 7

Yamaha Motif ES7

Yamaha Motif MS 7

Roland XP 50

Roland XP 80

Miscellaneous

3 guitar stands to be provided.

Lighting Requests:

At the end of "Another Way To Die": lights out on lead vocalist, and lights highlight piano: for Skyfall intro, as a new lead vocalist walks on to begin piece.

For the final song, "Uninvited/Kashmir": first a spotlight on Rique (1st vocalist) who will be alone onstage, then on Leah (2nd vocalists) who will come out and replace Rique at centerstage, then Steph and Kathryn (3rd and 4th vocalists) who will replace Leah at centerstage.